

The 2007 triennial edition of the California Code of Regulations, Title 24 (California Building Standards Code) applies to all occupancies that applied for a building permit on or after January 1, 2008, and remains in effect until the effective date of the next triennial edition. The following errata items will be officially published and distributed by ICC and IAPMO. (Note: Items shown underlined denote the errata item that was revised)

Errata items for the 2007 Triennial Edition of Title 24, Parts 2, 4, and 5 of the 2007 California Code of Regulations (CCR)

(Updated on 1-12-09)

• **Part 2 - California Building Code, Vol. 1 & 2**

- **Chapter 10** – Matrix Table Correction – Add an ‘X’ to the matrix adoption table for the HCD agency under Section number 1003.1.

- **Chapter 11A** – *Correct internal reference to Chapter 11A Figure 11A-6C.*

Section 1107A DEFINITIONS Immediately following the heading and before the first definition in this section there should be a sentence that reads;

For the purpose of this chapter, certain terms are defined as follows:

The last three headings for the 1107A definitions sections are shown incorrectly. The following is the correct order of these three items.

1107A.24-X (No definitions)

1107A.2425-Y (No definitions)

1107A.26-Z (No definitions)

Section 1114A.4.7 Other intermediate landings. *Other intermediate landings shall have a dimension in the direction of ramp run of not less than 60 inches (1524 mm). (See Figure ~~44-A66~~ 11A-6C).*

• **Part 4 – California Mechanical Code**

- **Chapter 4, Section 418.5 Alarm Systems.** *(Change the word “an” to “and” in the first sentence of the paragraph and change the word “cubit” to “cubic” at the end of the paragraph as follows)*

An Audible ~~an~~ and visual alarm system shall be installed to alert sterilizer operating personnel if the air flow falls below design ~~cubit~~ cubic feet per minute(L/S).

• **Part 5 – California Plumbing Code**

- **Table 4-1 Instructional Language** (Modification to clarify the use of a reference Table A)

Table 4-1

Minimum Plumbing Facilities¹

Each building shall be provided with sanitary facilities, including provisions for persons with disabilities as prescribed by the Department Having Jurisdiction¹⁹.
For requirements for persons with disabilities, Chapter 11A or 11B of the California Building Code shall be used.
~~The total occupant load shall be determined by the minimum existing requirements.~~ The minimum number of fixtures shall be calculated by fifty (50) percent male and fifty (50) percent female based on the total occupant load. The occupant load and use of building...

"Remaining language and exceptions for Table 4-1 are to remain as printed in the 2007 edition of the CPC".