



STATE OF CALIFORNIA  
Department of General Services - Office of Procurement

**PURCHASE ORDER**

Purchase Order No. **62173** Rev. **6/30/2008** Date

Form GSOP 1-PIN (04/98)

<b>Supplier No.</b> 39567	<b>Solicitation No.</b> 56972	<b>Delivery Date</b> 180 Days ARO	<b>FOB Point</b> Destination	<b>Invoice Terms</b>
<b>S</b> DEPT OF WATER RESOURCES <b>h T</b> 4300 WEST CAPITOL AVENUE <b>i o</b> WEST SACRAMENTO, CA 95691 <b>p</b>		<b>C</b> WATER RESOURCES A-36 <b>h a T</b> ATTN: ACCOUNTS PAYABLE <b>r o</b> PO BOX 942836 <b>g e</b> SACRAMENTO, CA 94236-001		
<b>Agency Billing</b> 81000	<b>Agency Purchase Estimate</b> 6000017833	<b>Purchase Estimate</b> 67095	<b>Revision</b> 0	
<b>Agency Contact</b> BILL MAHON		<b>Phone</b> 916-653-6167	<b>Date Received</b>	

HOLT OF CALIFORNIA  
7310 PACIFIC AVE  
PLEASANT GROVE, CA 95668  
Attn: ROD MCNABB

Phone: 916-991-8305

Item No.	Quantity	Unit	Commodity Code	Description	Unit Price	Extension
<p>The General Provisions for Non-IT Commodities are hereby incorporated by reference. These General Provisions can be obtained by phoning (916) 375-4400 or by accessing our website at:</p> <p><a href="http://www.documents.dgs.ca.gov/pd/modellang/GPnonIT0407.pd">http://www.documents.dgs.ca.gov/pd/modellang/GPnonIT0407.pd</a></p> <p>The following information is provided for agency use only:</p> <p>Small Business: NS Fiscal Year: 2007/2008</p>						
1	1	EA	2410-563-0101-2	TRACTOR TRACKLAYING (AS DESCRIBED)	275,843.4800	275,843.48
<p><u>CRAWLER DOZER, TRACKED</u> in accordance with:</p> <p>Crawler Dozer, Tracked, 184 HP Specification 2410-0210 of three (3) pages dated 6/25/2008.</p> <p>Crawler Dozer, Tracked, 184 HP Administrative Requirements of four (4) pages dated 6/26/2008.</p> <p>Crawler Dozer, Tracked 184 HP Questionnaire 6709TQ of two (2) pages dated 6/26/2008.</p> <p>Brand: <u>CATERPILLAR</u> Model: <u>D6T TIER 3</u></p>						
<b>Total Value:</b>						275,843.48
<p><u>F.O.B. Destination Requirement</u></p> <p>For the purpose of this award only F.O.B. destination will be accepted.</p>						

Sales and/or use tax to be extra unless noted above

Buyer <i>for Jim Mores</i> GUS QUINTERO	Phone 916-375-4499	BOC Number
---	-----------------------	------------

STATE OF CALIFORNIA

Department of General Services - Office of Procurement

**PURCHASE ORDER CONTINUATION**

Form GSOP 2-PIN (04/98)

<i>Purchase Order No.</i>	<i>Revision</i>	<i>Date</i>	<i>Supplier No.</i>	<i>Supplier Name</i>
62173		6/30/2008	39567	HOLT OF CALIFORNIA

<i>Item No.</i>	<i>Quantity</i>	<i>Unit</i>	<i>Commodity Code</i>	<i>Description</i>	<i>Unit Price</i>	<i>Extension</i>
<p><u>Delivery</u></p> <p>One hundred eighty (180) days after receipt of order (ARD).</p> <p><u>Addendums 1 and 2</u></p> <p>Are incorporated and now are part of this purchase order.</p> <p><u>Purchase Order Award</u></p> <p>This purchase order is being awarded on September 22, 2008 pursuant to Government Code Section 13332.17. Any encumbrances made pursuant to this purchase order shall be construed to have been made on the last day of the preceding fiscal year.</p> <p><u>Change Orders</u></p> <p>This Purchase Order may be amended, modified, or terminated at any time by mutual agreement of the parties, in writing. Change orders amending, modifying or terminating the Purchase Order, including any modifications of the compensation payable, may be issued only by the State Procurement Officer. All such change orders shall be in writing and issued only upon written concurrence of the supplier. Termination, as that term is used in this section, does not include termination for default of the supplier.</p> <p>This purchase order had been registered into the State Contract and Procurement Registration System (SCPRS) (<a href="https://www.scprs.dgs.ca.gov/">https://www.scprs.dgs.ca.gov/</a>). The registration number is: 38600908333681</p>						



STATE OF CALIFORNIA  
BID SPECIFICATION  
CRAWLER DOZER, TRACKED, 184 HP

2410-0210

**1 SCOPE**

This specification establishes the minimum requirements for a tracked crawler dozer utilized to maintain levees, channels and other flood control structures in areas with typical California ambient temperatures. The supplier is responsible for providing a tractor that meets the following minimum requirements.

**2 APPLICABLE SPECIFICATIONS / STANDARDS / CODES**

Specifications, standards and codes referenced in this document in effect on the opening of the 'Invitation For Bid', form a part of this specification. The vehicle furnished under these specifications shall conform to all of the requirements of all Divisions and Chapters of the following publications:

1. United States Code of Federal Regulations, Title 40, Part 89 (40CFR Part 89)
2. California Vehicle Code
3. Environmental Protection Agency and/or California Air Resources Board
4. Society of Automotive Engineers (SAE) and/or International Standards Organization (ISO)
5. Cal-OSHA safety requirements

**3 REQUIREMENTS**

**3.1 GENERAL**

The vehicle shall be new and equivalent in style, quality, and appointments to those offered to the general public. The vehicle shall be supplied with all equipment and accessories indicated as standard equipment in the manufacturer's published literature. Optional equipment necessary to meet the requirements of this specification shall also be installed. The vehicle shall meet the following requirements:

- Overall Vehicle Length (with winch): 23 ft. (maximum)
- Overall Vehicle Height: 11 ft. (maximum)
- Overall Vehicle Width (without blade): 9 ft. (maximum)
- Track Gauge: 75 in. (minimum)
- Track Length on the Ground: 112 in. (minimum)
- Ground Pressure: 9.5 psi (maximum)
- Ground Clearance: 15 in. (minimum)
- Maximum Draw Pull Rating of Tractor: 65,000 lbs. (minimum)

**3.2 ENGINE**

The vehicle shall be equipped with the manufacturer's standard diesel engine that meets the following minimum requirements:

- Power: 184 net hp per SAE J1394 (minimum)
- Torque: 560 lbs.-ft. (minimum)
- EPA Tier 3 Certification
- Fuel Tank: 80 gal. (minimum)

The engine shall be equipped with, but not limited to, the following accessories:

- A variable speed engine governor, factory set to the engine manufacturer's recommended RPM for tractor applications.
- Cold weather starting aid
- The air cleaner shall be a 2-stage unit with a centrifugal pre-cleaner stage and two replaceable, dry element type final stage filters. An air restriction gauge shall be supplied, preferably mounted in the cab.

The tractor shall be equipped with visual and/or audible warning devices, in addition to the gauges, to alert the operator of conditions critical to the engine and equipment operation. The tractor's operating station shall be equipped with, but not limited to, the following engine monitoring and instrumentation warning devices:

- Engine Oil Pressure (gauge and critical warning)
- Engine Coolant Temperature (gauge and critical warning)
- Transmission Oil Temperature (gauge and critical warning)
- Hydraulic Oil Temperature (gauge and critical warning)
- Engine Hour Meter

- Fuel Level
- System Voltage

### 3.3 TRANSMISSION

The transmission shall have a minimum of three (3) forward speeds and three (3) reverse speeds OR an infinitely variable transmission. The tractor shall be capable of traveling 6.25 mph or higher. The tractor shall be equipped with a transmission safety device that will prevent the engine from starting or prevent the machine from moving if the engine is started while the transmission is engaged.

### 3.4 TRACK ASSEMBLY

The track shoe width shall not be less than 24 inches wide and all the shoes shall be the same size. Each track assembly shall provide a minimum ground contact area of 2400 square inches for a total contact area of not less than 4800 square inches. The track supplied shall be the manufacturer's extreme service or heavy-duty type.

### 3.5 STEERING

The tractor shall provide full power steering. The steering shall allow for full power turns at speed.

### 3.6 BRAKES

The tractor shall be equipped with a foot operated, power braking system. A parking brake shall be installed and may be connected to the service brakes or operated independently on the drive shaft or transmission output shaft. A warning light shall be installed on the instrument panel in full view of the operator to indicate that the parking brake is applied while the engine is running.

### 3.7 CAB

The tractor shall be equipped with a fully enclosed cab. The cab shall be constructed to afford the operator visibility for the entire operation. The cab shall be completely sealed and pressurized to protect the operator from the external environment. In addition to the fully enclosed cab, the operator shall be protected by a Rollover Protective Structure (ROPS) certified by the manufacturer to conform to the requirements of SAE J1194 Standard "Rollover Protective Structures for Wheeled Agricultural Tractors." The cab shall also provide a Falling Object Protection Structure (FOPS) in accordance with ISO 3449-1992 Level II as a minimum. A combination cab and safety guard approved by the Division of Industrial Safety will be acceptable. In general, the cab shall provide maximum operator protection and comfort.

The following items, supplementing if necessary those items already cataloged as standard cab equipment, shall be furnished and installed:

- 3.7.1 Decelerator Pedal
- 3.7.2 Safety glass windows
- 3.7.3 Sun visors
- 3.7.4 Key-type locking door(s)
- 3.7.5 Padded suspension high back type seat, adjustable arm rests, and seat belt
- 3.7.6 Adjustable joy stick style controls for both travel and blade control
- 3.7.7 AM/FM radio with weather band and speakers
- 3.7.8 12-volt power supply
- 3.7.9 Front windshield wiper and washer
- 3.7.10 Interior rear view mirror
- 3.7.11 Outside rear view mirrors
- 3.7.12 Horn
- 3.7.13 Forestry type wire mesh window screens/guards for side and rear windows (minimum).
- 3.7.14 Cab brush Guards (also known as "Limb Risers" or "Logging Sweeps")

### 3.8 AIR CONDITIONING

A multi-speed cab heater, air conditioning and windshield defroster shall be included. The system shall come equipped with fresh air ventilators or combination fresh air and recirculating ventilation system. The system shall include a HEPA filtration system capable of filtering out normal particulate encountered during roadside mowing operations (e.g., dust, pollen, etc.).

**3.9 ELECTRICAL SYSTEM**

The electrical system shall comply with all Federal and State regulations. The system voltage shall be 12 Volt and include a minimum of two (2) maintenance free type batteries with a minimum 650 CCA at 0° F each. The tractor will come equipped with the following lighting as a minimum:

- 360 Degree lighting for nighttime operation
- Strobe light

**3.10 HYDRAULICS**

The hydraulic system shall utilize a replaceable element (spin-on type) with filtering capability of 10 microns or less. The pump that operates the equipment shall be of sufficient capacity to safely permit the simultaneous operation of at least two controls. The system shall have adequate cooling to operate in high ambient temperatures.

**3.11 EQUIPMENT**

3.11.1 Dozer Blade: The blade shall be a hydraulically actuated PAT dozer type blade with lift, angle and tilt controls and a capacity of not less than 5.0 cubic yards. The six-way blade shall be suitable for finish grading, ditching and backfilling. The blade shall be equipped with a full length, multiple section, replaceable cutting edge and shall meet the following:

- Lift Height: 42 in. (minimum)
- Blade Height: 47 in. (minimum)
- Blade Width: 142 in. (minimum)
- Depth of Cut: 26 in. (minimum)
- Blade Tilt: 17 in. (minimum)

3.11.2 Drawbar: A standard clevis type drawbar shall be supplied and mounted at the rear of the tractor. An auxiliary hydraulic circuit with cab-mounted controls shall be provided at the rear of the tractor that will be used to operate implements such as a disc connected to the drawbar.

3.11.3 Winch: A rear mounted, 44,000 lb. minimum draw pull winch with cab mounted controls for the hydraulic valve shall be supplied (reference Allied model W6G or WH6G or equivalent). The winch shall include a 4-roller fairlead and the largest diameter wire rope recommended for the winch model. The winch shall be capable of powering the line in and out while the tractor is in motion and shall have a brake and free spool function.

3.11.4 The tractor shall be supplied with counter weights as necessary to optimize the machine performance.

**3.12 PAINT**

The cab, hood and fenders shall be finish painted with the manufacturer's standard lead-free enamel paint (lead-free: 100-PPM maximum based on dry paint). The finish coat shall be free from runs, drips, sags, etc., and shall be evenly applied to provide a gloss finish.

**3.13 MISCELLANEOUS**

The following miscellaneous equipment shall be furnished and installed:

- Vandal Protection Package: Vandal protection shall include the engine compartment, battery compartment, and all fluid fill ports. All locks shall be keyed alike and four sets of keys shall be supplied.
- Front pull hook
- Crankcase/Transmission rock guard
- Heavy duty radiator (with guard)
- Reversible hydraulic radiator fan
- Full length track roller guards
- Final drive guard
- Removable Slow Moving Vehicle sign

**3.14 OPTIONAL EQUIPMENT**

Provide as a separate item, the costs for the following option that may be ordered with the standard machine described in the previous sections of this specification:

- Grade Control System Ready Option: the option shall include all mounts and hardware for equipment, electrical harnesses, switches, electronics, and hydraulics to support "plug and play" capability of the grade control system components. The grade control system ready option shall be compatible with a Trimble model GCS400, Topcon "Dozer System 4," or comparable.



STATE OF CALIFORNIA  
ADMINISTRATIVE REQUIREMENTS  
CRAWLER DOZER, TRACKED, 184 HP

67095AR

**1 REGISTRATION**

The original dealer's "Report of Sale" shall be furnished by all California licensed dealers at the time of delivery of each unit or units covered by these specifications. A "Manufacturer's Statement of Origin" and original "Bill of Sale" on the vendor's letterhead may be supplied for each unit in lieu of a dealer's Report of Sale, if the supplier is not a registered California dealer. An original weight certificate from a California Weigh Master for registration purposes must be supplied at the time of delivery of each unit. A Federal Excise Tax Exempt Certificate will be attached to the purchase order. All documentation supplied for registration shall contain the following physical and post office box addresses:

State Department Water Resources  
1416 9th Street  
Sacramento, CA 95814

State Department Water Resources  
P.O. Box 942836  
Sacramento, CA 94236-0001

All required documentation shall be sent to one of the above addresses by the time of delivery.

NOTE: The State shall register/license all vehicles with the Department of Motor Vehicles.

**2 BOOKS AND MANUALS**

One (1) set of standard operator's manual, complete lubrication instructions, parts books and shop repair manuals (complete with electrical and hydraulic schematics) shall be supplied with each unit. On receipt of the first units, one (1) additional set of manuals shall be supplied for the State files.

**3 WARRANTY**

The unit(s), including but not limited to the chassis, engine, drive train, electrical system and all modifications made to the unit prior to delivery, etc., shall be covered (parts and labor) under a factory authorized extended warranty for one (1) years or 1000 engine hours, whichever occurs first, following the date the Department puts the unit into service. The Department will notify the supplier by mail of the in-service date and keep a record of the in-service date.

The warranty shall cover 100 percent parts and labor of all repair costs, the entire unit, including modifications and any optional equipment or accessories being supplied. A copy of the manufacturer's warranty for the unit and any accessory or optional equipment shall be supplied with each unit.

**4 SAFETY**

The entire unit and accessories shall comply with the applicable provisions of the California Vehicle Code, the Safety Orders of the Division of Industrial Relations, and all Federal regulations in effect at the time of manufacture. The loader shall be equipped with a removable, rear mounted "Slow Moving Vehicle" identification emblem in accordance with the California Vehicle Code, Division 12, Chapter 2, Article 3, Section 24615.

**5 TRAINING**

The supplier, at his expense, shall provide a qualified factory authorized service representative (not a salesman) to provide training for operators, mechanics, and parts personnel. This training (not a sales presentation) shall consist of hands on operation, safety, service, and adjustments for the operators; mechanical repair and adjustment specifications for the shop and field mechanics; parts manual orientation, nomenclature and ordering procedures for parts personnel.

A training plan outline, containing at least all of the subjects listed above, shall be submitted for approval within 30 days after receipt of the order (ARO) to the Transportation Office Senior Automotive Inspector at (916) 653-9051.

The training shall be provided at the Division of Flood Management's Sutter Maintenance Yard located in Sutter California. This training shall be for one (1) 8 hour day (or longer as the supplier or State deems necessary), and the date(s) of the training will be arranged by the Transportation Office at (916) 653-9051. The full cost of this service shall be included in the bid. All training shall be accomplished within 45 days of acceptance and receipt of the unit unless otherwise mutually agreed to between the supplier and the Senior Automotive Inspector.

## 6 INSPECTION

This order will require a two (2) phase inspection process. For all inspections the unit will be serviced, washed and ready for, as applicable, inspection or delivery. Inspections will begin within five (5) working days from the date of the inspection request by the supplier. It is the supplier's responsibility to contact DWR's Transportation Office for inspections at (916) 653-9051.

FIRST PHASE (PRE-DELIVERY INSPECTION): In accordance with the State Administrative Manual, Section 4112 and the Department of Water Resource's Transportation Office inspection program, the unit will be inspected prior to shipment to the destination on the purchase order. This inspection trip shall be State financed at no cost to the supplier.

The unit shall be identified with the applicable Purchase Order Number. If corrections are needed as a result of the inspection, the corrections shall be made prior to shipment to the purchase order destination. Authorization to deliver the unit must be granted by the Department of Water Resources, Division of Management Services, Transportation Office.

If additional interim inspections are required, such inspection trips shall be at the expense of the supplier at \$75.00 per hour (including travel time) and all expenses (meals, lodging, and cost of transportation). Travel expenses will be documented on State of California, Travel Expense Claim Form, FA302. These fees may be deducted from the invoice.

PRE-DELIVERY INSPECTION LOCATION: The inspection shall be conducted by the Department of Water Resources, Division of Management Services, Transportation Office. These inspections shall take place at an adequate site provided by the vendor within the State of California. The inspection site shall meet all of the following criteria:

- a. The site shall not be the Purchase Order delivery destination. The site shall be paved, secure and zoned for commercial use.
- b. The site shall include electricity, lights, water, compressed air and a secure paved lot. The facilities shall also include lift equipment adequate to raise the units and support them on safety stands with a minimum of 12 inches of tire clearance. The supplier shall provide conditions which meet the safety standards of CAL-OSHA and Title 8 of the California Code of Regulations.
- c. The adequacy of the site shall be determined by the Department of Water Resources, Division of Management Services, Transportation Office. Contact the Senior Inspector of Automotive Equipment at (916) 653-9051.
- d. If the facility is deemed unacceptable by Department of Water Resources, Division of Management Services, Transportation Office, the vendor shall be billed for the inspection trip including wages and expenses. This cost shall be deducted from the purchase order payment.

SECOND PHASE (FINAL INSPECTION): Each unit will have a final inspection at its delivery destination shown on the Purchase Order to verify acceptability. The State will have five (5) working days after delivery of a unit to conduct the final inspection of said unit. A unit delivered to the final Purchase Order destination will be accepted only when all Purchase Order requirements have been met, any shipping damages have been corrected, and all required documents are received by the Department of Water Resources, Division of Management Services, Transportation Office. These documents include, as applicable, the invoice, vehicle registration documents, parts book, operator's manuals, service manuals, lubrication instructions and charts, warranty information, certifications, questionnaires, etc. A unit which is not accepted by the delivery date on the Purchase Order will be considered delivered late.

If the supplier receives notice that the unit is not acceptable, whether written or oral, the unit shipped to the Purchase Order destination shall be removed within seven (7) calendar days. If the supplier fails to remove said

unit from the State's facilities within the specified period, the State may forward said unit to the supplier by common carrier at the supplier's expense and risk.

## 7 DELIVERY

Inspection, delivery, and final acceptance of the unit on the Purchase Order shall be within 180 calendar days after the Purchase Order date. Contact the State of California, Department of Water Resources, Division of Operations and Maintenance, Transportation Office at (916) 653-9051 for delivery.

Failure of any units to comply with the specifications by the final delivery date may place the supplier in default and may be grounds for the State to invoke Paragraph 26 of the General Provisions, Rights and Remedies of the State for Default. The Department of General Services, Procurement Division will be notified at such time.

Acceptance of delivery or placement in operation of any equipment shall not release the manufacturer from liability for faulty design, workmanship, or materials appearing even after final payment has been made.

## 8 LATE DELIVERY CHARGES

The parties to this agreement acknowledge that the State shall incur actual damages should the supplier fail to perform the work as called out in the contract and specification on the dates set forth herein. The parties, therefore, have agreed to late delivery charges in the amount of \$75.00 per unit per workday.

Workdays are Monday through Friday inclusive, except State holidays observed Monday through Friday inclusive.

The parties also agree that the amount specified is not unreasonable nor punitive in nature because both parties have carefully considered the amount specified and believe it to be a reasonable estimate, and not excessive at the time the purchase order is entered into.

It is, therefore agreed, that the supplier will pay the State of California the sum of \$75.00 per unit per work day (as stated above) for each work day the work remains uncompleted or unaccepted by the State, provided the total late delivery charges assessed against supplier shall in no event exceed twenty-five percent

(25%) of the total value of the entire order, and the supplier agrees to pay said damages as herein provided. In the event such damages are not paid, the supplier agrees that the State may deduct the amount thereof from any monies due or that may become due said supplier.

## 9 PAYMENT

Process for payment will be initiated on each unit as units are received and deemed acceptable. The discount period will start after acceptance of each unit on the Purchase Order.

## 10 QUESTIONNAIRE

The attached questionnaire shall be filled out and will become a part of each bid submitted. Any portion of the questionnaire which is not applicable to the equipment shall be shown as N/A (not applicable). Failure to submit a completed questionnaire may result in rejection of your bid.

Unless otherwise stated in the purchase order, the requirements of the written purchase order specification shall have precedence over the completed questionnaire; and the completed questionnaire shall have precedence over standard factory specifications or literature.

## 11 GENERAL

One (1) complete set of filters (air, oil, water, fuel, hydraulic, etc.) shall be supplied with all units delivered. This set of filters shall be as recommended by the manufacturer and shall be complete with the appropriate part numbers for identification.

Each unit and any accessory shall be delivered completely assembled and ready to operate.

No exceptions to the specifications will be allowed unless the exceptions are listed on the purchase order or subsequent addenda.

The component parts of the unit shall be new and of proper size and design to safely withstand the maximum stresses imposed.

The manufacturer's torque rating of each driven part shall be equal to or exceed the torque rating of its driving member.

Complete printed specifications, published literature, and photos or illustrations of unit or units that the bidder proposes to furnish shall be supplied upon request.

All equipment and accessories cataloged as standard, unless superseded by these specifications, are to be furnished and included in purchase price of this unit.

Bids will be considered only on equipment represented by a supplier capable of providing adequate repair parts, warranty, technical assistance, and training in the United States as of the bid opening date. The supplier shall be capable of supplying repair parts to within five (5) working days after a purchase order for parts is submitted to the supplier, whether by phone, fax, or mail.

Bidders may be required to provide documentation supporting this requirement prior to award of the contract.

Suppliers shall be the equipment manufacturer, an authorized factory dealer or representative thereof, or shall have authorization from the equipment manufacturer or authorized factory dealer to solicit the equipment bid. The bidder shall be capable of providing parts, service, warranty, and training for the equipment bid as specified herein. If the bidder cannot provide these items for the equipment bid, the equipment manufacturer or an authorized factory dealer may provide these items for the bidder. Upon request, the signed agreement between the bidder and the equipment manufacturer or authorized factory dealer, stating who will be responsible for providing parts, service, warranty, and training for the equipment bid, shall be provided to the State.

Bids will not be considered if supplier's designated f.o.b. delivery destination is other than the delivery address stated in the invitation to bid.

Only new models in current production, which are cataloged by the manufacturer and for which manufacturer's published literature and printed specifications are currently available, will be considered. Special options may be included only when recommended by the manufacturer of the unit and approved by the State.

All equipment/options are to be factory installed. If the equipment/options are not available factory installed, dealer installed equipment/options may be acceptable. The bidder is to specify those items which will be dealer installed.

The State reserves the right to amend the contract up to 10% of the purchase order price to cover deficiencies or inconsistencies within or between the technical specifications and or drawings. These amendments shall cover the cost of any materials involved and or the standard shop labor rate for modification or installation.

The State reserves the right to purchase a minimum of one (1) additional unit at bid prices, for State Agencies and California Local Government Agencies. Orders for such additional units shall be placed within 120 days of bid award date.

## 12 CHANGE ORDERS

This contract may be amended, modified, or terminated at any time by mutual agreement of the parties. Change orders amending, modifying, or terminating the contract including any modification of the compensation payable, may be issued only by the State Procurement Officer and shall be in writing. Termination, as that term is used in this section, does not include termination for default of the supplier.



STATE OF CALIFORNIA  
 BID SPECIFICATION  
 CRAWLER DOZER, TRACKED, 184 HP

67095TQ

QUESTIONNAIRE

For the bid to be considered complete, the following questionnaire must be filled out and submitted with the bid package.

Bidder: Holt of Calif Solicitation #: 56972  
 Make: Caterpillar Model: DBT

Date: 8-1-08

GENERAL:	Overall Vehicle Length (with winch): Overall Vehicle Height: Overall Vehicle Width (without blade): Track Gauge: Track Length on the Ground: Ground Pressure: Ground Clearance: Maximum Draw Pull Rating of Tractor:	<u>19.33</u> ft. <u>10'6"</u> ft. <u>8'10"</u> ft. <u>84</u> in. <u>113</u> in. <u>8.93</u> psi. <u>15</u> in. <u>77,800</u> lbs.
ENGINE:	Power: Torque: EPA Emissions Type: Fuel Tank: Cold weather starting aid included	<u>198</u> HP <u>920</u> lb.-ft. <u>Tier 3</u> <u>112</u> gal. <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No
TRANSMISSION:	Transmission type: Forward speeds: Reverse speeds: Maximum forward speed:	<u>Planetary</u> <u>5</u> Speeds <u>5</u> Speeds <u>7.11</u> MPH
TRACK:	Shoe Width: Total Contact Area:	<u>22</u> in. <u>4972</u> in. <sup>2</sup>
CAB:	Decelerator Pedal Safety glass windows Sun visors Key-type locking door(s) Padded suspension high back type seat, adjustable arm rests Joy stick style controls for both travel and blade control AM/FM radio with weather band and speakers 12-volt power supply Front windshield wiper and washer Interior rear view mirror Outside rear view mirrors	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No

No credits

Planetary Power Sh. As

	Horn	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No
	Mesh window screens/guards for side and rear windows (minimum).	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No
	Cab brush Guards (also known as "Limb Risers" or "Logging Sweeps")	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No
AIR CONDITIONING:	HEPA filtration: <i>Advanced Filtration</i>	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No
ELECTRICAL:	Alternator current rating:	<u>95</u> Amps.
	Number of batteries	<u>2</u>
	Cold Cranking Amp rating of the batteries (total):	<u>1000</u> CCA
	360° Lighting Package?	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No
DOZER BLADE:	Capacity:	<u>4.73</u> yd. <sup>3</sup>
	Lift Height:	<u>46</u> in.
	Blade Height:	<u>51</u> in.
	Blade Width:	<u>12.73</u> in.
	Depth of Cut:	<u>29</u> in.
	Blade Tilt:	<u>17</u> in.
WINCH:	Maximum pull:	<u>89800</u> lbs.
MISCELLANEOUS:	Vandal protection package:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No
	Front pull hook	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No
	Crankcase/Transmission rock guard	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No
	Heavy duty radiator (with guard)	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No
	Reversible hydraulic radiator fan	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No
	Full length track roller guards	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No
	Final drive guard	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No
	Removable Slow Moving Vehicle sign	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No